


AirStream V

saugend . suction

drückend . compression

AirTec
SISTEMAS
 División Aquabona,SL

Distribuidor España
 Tel: +34932010867
 info@airtecsistemas.com
 www.airtecsistemas.com



896295000008P

Module for suction or compression evaporators, placement directly before the air outlet of the evaporator, module made from stainless steel 1.4301, functional check via inspection window with UV protection filter, module access via inspection lid, UV-C emitter with special interior coating of the quartz glass for long service life with low irradiation fall-off, number and rating of the UV-C emitters dependent on the required air flow rate

UV-C technology

Number of emitters	project-related
Emitter type	289503A(T)
Emitter power	95 W
Protection rating . Protection class	IP 20 . I
Emitter service life	9,000 h

Areas of deployment

All evaporators without humidification

Unit geometry

Width	project-related
Length	
Height	

Project planning

Each module is individually designed for the existing or planned evaporator and precisely customised in terms of performance and dimensions

Performance data

Supply voltage	230 V
Frequency	50-60 Hz
Power consumption	project-related
Air flow rate	as per evaporator project planning

Note

A special Teflon coating of the UV-C emitters guarantees optimum radiant efficiency even at low temperatures

Accessories . Options

Tube connecting sleeves
 Protection rating IP 65