



**890260AT**  
 incl. UV-C compact emitter

**890260TAT**  
 incl. UV-C compact emitter  
 with Teflon sheath

Air disinfection unit for rooms  
 with integrated evaporators,  
 ceiling mounting, placement  
 directly in front of the evapo-  
 rator air outlet for disinfection  
 of a partial airflow, housing  
 made of stainless steel  
 1.4301, UV-C emitter with  
 special interior coating of the  
 quartz glass for long service  
 life with low irradiation  
 fall-off, optional UV-C emitter  
 with Teflon sheath

<b>UV-C technology</b>	
Number of emitters	2
Emitter type	28600A(T)
Emitter power	2 x 60 W
UV-C output	38 W
Protection rating . Protection class	IP 20 . I
Emitter service life	9,000 h

**Areas of deployment**  
 Store rooms with evaporator  
 coolers

<b>Unit geometry</b>	
Length	1,000 mm
Diameter	250 mm
Weight	9.2 kg

**Project planning**  
 Number of units to be used  
 depends on the evaporators  
 deployed in the store room

<b>Performance data</b>	
Supply voltage	230 V
Frequency	50-60 Hz
Power consumption	140 W

**Note**  
 The unit emits UV-C  
 radiation, which is why it  
 needs to be switched off  
 before entering the room

**Accessories . Options**  
 UV-C emitter with Teflon sheath